

NOTE: FOR USE ON SLOPES 2:12 OR GREATER.
 NOTE: REQUIRES FLOATING EAVE AND VALLEY.

Legend


As Supplied By ATAS:

- 1 - ATAS FLS Panel
- 2 - Anchor Clips
- 4 - Painted Pop Rivets
- 12 - Hip Cap (Fixed)

As Supplied By Others:

- A - 30# (Minimum) Felt with Rosin Paper
 - A1 - 40 MIL Ice & Water Shield
 - B - Top of Roof Deck or Insulation
 - C - Structurals
 - D - Trim Boards
 - E - #12 x 1" Wafer Head Screws
 - E1 - #12 x 1-1/4" Hex Head Screws
 - F - Fascia Trim (May be fabricated/supplied by ATAS upon request).
 - G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
 - H - Appropriate Sealant
 - L - Plywood
 - U - Butyl Tape Sealant
 - V - Support Plate - 18 ga.
 - WS - Wood Shim 3/8" or 1-3/8"
- * - Indicates color side.

Field Lock
 Hip Detail (Fixed) Scale: 3" = 1'-0"

		ATAS INTERNATIONAL, INC. Allentown PA 610-395-8445 Mesa AZ 480-558-7210	
TITLE			
FLS Hip (Fixed) - ply			
DWG NO. / FILE NO.		FLS Hip (Fixed) - ply	
SCALE		3"=1'-0"	
DRAWN BY	DAS	DATE	3-6-06
APPR. BY	JEB	DATE	6-1-06
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY
APPR. BY	XXXX	APPR. DATE	MM/DD/YY

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	FLS Hip (Fixed) - ply