



ATAS INTERNATIONAL, INC.

SPECIFICATION DATA SHEET

1. PRODUCT NAME

MULTI-PURPOSE PANEL™

2. MANUFACTURER

ATAS INTERNATIONAL, INC.

Website: www.atas.com

Email: info@atas.com

Corporate Headquarters:

Allentown, PA 18106

Phone: (610) 395-8445

Fax: (610) 395-9342

Western Facility:

Mesa, AZ 85204

Phone: (480) 558-7210

Fax: (480) 558-7217

Southern Facility:

Maryville, TN 37801

Phone: (800) 468-1441

3. PRODUCT DESCRIPTION

Basic Uses:

Multi-Purpose panels with the Wind-Lok application have a smooth, sleek appearance with a concealed, clipless fastening system. These panels are typically used for siding, fascias, mansards and equipment screens.

Composition & Materials:

Standard Offerings: Panels are roll-formed from .032 or .040 Aluminum or 24 gauge Metallic Coated Steel. **Special Offerings:** 22 gauge Metallic Coated Steel.

Sizes and Profiles:

Four 8" wide panels, seven 12" wide panels and six 16" wide panels are available. The semi-standing seam (MPN code), the batten style (MPW code) and the plank or barn board (MPH code) give completely different appearances. A slight "V" in the MPH series gives another variation in style (MPV code). Panel lengths are cut to customer specifications.

Colors & Finishes:

A choice of 30 colors is available in a KYNAR 500® PVDF or HYLAR 5000® PVDF finish. (Request color chart or chips). An anodized finish is available in Clear or Dark Bronze. Texture may be smooth or stucco embossed.

4. TECHNICAL DATA

KYNAR 500® PVDF or HYLAR 5000® PVDF based finishes tested by paint supplier for:

Dry Film Thickness: ASTM D 1005, ASTM D

1400, ASTM D 4138 or ASTM D 5796

Specular Gloss: ASTM D 523

Pencil Hardness: ASTM D 3363

T-Bend Flexibility: ASTM D 4145

Mandrel Bend Flexibility: ASTM D 522

Impact Resistance: ASTM D 2794

Adhesion: ASTM D 3359 Water Immersion Resistance: ASTM D 870

Abrasion Resistance: ASTM D 968

Acid Resistance: ASTM D 1308

Acid Rain Resistance (Kesternich):

ASTM G 87 or DIN 50018

Salt Spray: ASTM B 117

Cyclic Salt Spray: ASTM D 5894 and ASTM D 5487

Humidity Resistance: ASTM D 2247

Accelerated Weathering: ASTM D 822 and

ASTM G 23, ASTM G 151 or ASTM G 153

Color Retention, Florida Exposure:

ASTM D 2244

Chalking Resistance – ASTM D 4214

Cleveland Condensing Cabinet: ASTM D 4585

Cure Test, MEK Resistance: ASTM D 5402

Alkali Resistance, Sodium Hydroxide: ASTM D 1308, Procedure 7.2

Flame Spread Rating: ASTM E 84

Organic coatings meet requirements of AAMA 2605 when applied to aluminum.

Panel testing/ratings:

UL 580 Class 90 (UL File No. R121123)

Air Infiltration: ASTM E 283

Water Penetration: ASTM E 331

Wind Driven Rain: AAMA 501.1

Fire Resistance: UL 790/ASTM E 108

Class A & B Fire Rating

Galvanized Steel: ASTM A 653

Aluminum: ASTM B 209

Coil Coating: ASTM A 755

Field Tested and Approved

Load Tables available upon request.

5. INSTALLATION

Installation is achieved by interlocking the panel into the preceding panel and fastening with mechanical fasteners.

The rib of the adjoining panel will conceal the fasteners. Installation manuals or hands-on training via seminars are available through ATAS. Visit www.atas.com for more information.

6. AVAILABILITY & COST

Availability:

Multi-Purpose panels are available through ATAS product distributors. A complete line of related components and trim accessories is available to complete the roof or wall system. In addition, a complete line of rainware and perimeter roof edge trims can be supplied by ATAS to complement the wall system. Flat sheet and/or coil stock is available in matching

color for fabrication of related components by the installing contractor.

Cost:

Contact ATAS product distributors for current pricing.

7. WARRANTY

Products coated with a fluoropolymer, KYNAR 500® PVDF or HYLAR 5000® PVDF finish carry a thirty (30) year limited warranty against chipping, cracking, peeling, chalking and fading.

8. MAINTENANCE

Multi-Purpose panels are virtually maintenance free. Surface residue may be easily removed by conventional cleaning methods. Minor scratches may be touched up with a matching paint, available from the manufacturer.

9. TECHNICAL SERVICES

Complete technical information and literature are available at www.atas.com. ATAS will assist with design ideas and shop drawings.

10. FILING SYSTEM

- www.construction.com
- www.atas.com
- Additional product information is available from the manufacturer upon request.

