

\* VARIES WITH ROOF PITCH

NOTE: USE ON SLOPES LESS THAN 2:12.

NOTE: REQUIRES FIXED EAVE AND VALLEY.

**Legend**

As Supplied By ATAS:

- 1 - ATAS FLS Panel
- 2 - Anchor Clips
- 4 - Painted Pop Rivets
- 11A - Ridge Cap (Floating)
- 13 - Neoprene Closure

As Supplied By Others:


- A - 30# (Minimum) Felt with Rosin Paper
- A1 - 40 MIL Ice & Water Shield
- B - Top of Roof Deck or Insulation
- C - Structurals
- D - Trim Boards
- E - #12 x 1" Wafer Head Screws
- E1 - #12 x 1-1/4" Hex Head Screws
- F - Fascia Trim ( May be fabricated/supplied by ATAS upon request).
- G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
- L - Plywood
- U - Butyl Tape Sealant
- WS - Wood Shim 3/8" or 1-3/8"

\* - Indicates color side.

Field Lock  
Ridge Detail (Floating)

Scale: 3" = 1'-0"

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	<b>FLS Ridge (Floating) - ply</b>

				<b>ATAS INTERNATIONAL, INC.</b> Allentown PA 610-395-8445 Mesa AZ 480-558-7210			
<b>TITLE</b>							
<b>FLS Ridge (Floating) - ply</b>							
DWG NO. / FILE NO.				SCALE			
<b>FLS Ridge (Floating) - ply</b>				<b>3"=1'-0"</b>			
DRAWN BY	DAS	DATE	3-6-06	APPR. BY	JEB	DATE	6-1-06
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY	APPR. BY	XXXX	APPR. DATE	MM/DD/YY