

Legend

As Supplied By ATAS:


- 1 - ATAS FLS Panel
- 2 - Anchor Clips
- 3 - Optional Metal Seam End Plugs
- 67 - Cinch Strap
- 68 - Backup Channel

As Supplied By Others:

- A - 30# (Minimum) Felt with Rosin Paper
- A1 - 40 MIL Ice & Water Shield
- B - Top of Roof Deck or Insulation
- C - Structurals
- D - Trim Boards
- E - #12 x 1" Wafer Head Screws
- F - Fascia Trim (May be fabricated/supplied by ATAS upon request).
- G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
- L - Plywood
- U - Butyl Tape Sealant
- V - Eave Plate

* - Indicates color side.

Field Lock
Panel Splice Detail (Floating) Scale: 3" = 1'-0"

		ATAS INTERNATIONAL, INC. Allentown PA 610-395-8445 Mesa AZ 480-558-7210	
TITLE			
FLS Panel Splice (Floating)			
DWG NO. / FILE NO.		SCALE	
FLS Panel Splice (Floating)		3"=1'-0"	
DRAWN BY	DAS	DATE	3-6-06
APPR. BY	JEB	DATE	6-1-06
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY
APPR. BY	XXXX	APPR. DATE	MM/DD/YY

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	FLS Panel Splice (Floating)