

NOTE: USE ON SLOPES
LESS THAN 2:12.
NOTE: REQUIRES FIXED
EAVE AND VALLEY.

Legend

As Supplied By ATAS:

- 1 - ATAS FLS Panel
- 2 - Anchor Clips
- 4 - Painted Pop Rivets
- 8 - Standard "Z" Closure
- 13 - Neoprene Closure


As Supplied By Others:

- A - 30# (Minimum) Felt with Rosin Paper
- A1 - 40 MIL Ice & Water Shield
- B - Top of Roof Deck or Insulation
- C - Structurals
- D - Trim Boards
- E - #12 x 1" Wafer Head Screws
- E1 - #12 x 1-1/4" Hex Head Screws
- F - Fascia Trim (May be fabricated/supplied by ATAS upon request).
- G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
- L - Plywood
- U - Butyl Tape Sealant
- WS - 3/8" Wood Shim

* - Indicates color side.

**Field Lock
Shed Ridge Detail
(Floating)**

Scale: 3" = 1'-0"

		ATAS INTERNATIONAL, INC. Allentown PA 610-395-8445 Mesa AZ 480-558-7210			
TITLE					
FLS Shed Ridge (Floating) - ply					
DWG NO. / FILE NO.		FLS Shed Ridge (Floating) - ply		SCALE 3"=1'-0"	
DRAWN BY	DAS	DATE	3-6-06	APPR. BY	JEB
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY	APPR. BY	XXXX
0	6-1-06	DAS	FLS Shed Ridge (Floating) - ply	DATE	6-1-06
				DATE	MM/DD/YY

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	FLS Shed Ridge (Floating) - ply