



* VARIES WITH ROOF PITCH

NOTE: USE ON SLOPES LESS THAN 2:12.

NOTE: REQUIRES FIXED EAVE AND VALLEY.

Legend

- As Supplied By ATAS:
 1 - ATAS FLS Panel
 2 - Anchor Clips
 4 - Painted Pop Rivets
 12A- Hip Cap (Floating)

As Supplied By Others:

- A - 30# (Minimum) Felt with Rosin Paper
 A1 - 40 MIL Ice & Water Shield
 B - Top of Roof Deck or Insulation
 C - Structurals
 D - Trim Boards
 E - #12 x 1" Wafer Head Screws
 F - Fascia Trim (May be fabricated/supplied by ATAS upon request).
 G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
 L - Plywood
 U - Butyl Tape Sealant
 V - Support Plate
 WS - 3Wood Shim 3/8" or 1-3/8"

* - Indicates color side.

Field Lock
 Hip Detail (Floating) Scale: 3" = 1'-0"

		ATAS INTERNATIONAL, INC. Allentown PA 610-395-8445 Mesa AZ 480-558-7210	
TITLE			
FLS Hip (Floating) - ply			
DWG NO. / FILE NO.		FLS Hip (Floating) - ply	
SCALE		3"=1'-0"	
DRAWN BY	DAS	DATE	3-6-06
APPR. BY	JEB	DATE	6-1-06
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY
APPR. BY	XXXX	APPR. DATE	MM/DD/YY

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	FLS Hip (Floating) - ply