

NOTE: USE ON SLOPES
2:12 OR GREATER.

NOTE: REQUIRES FLOATING
RIDGE AND VALLEY.

Legend

As Supplied By ATAS:


- 1 - ATAS FLS Panel
- 2 - Anchor Clips
- 4 - Painted Pop-Rivet
- 8 - Standard "Z" Closure
- 13 - Neoprene Closure
- 17 - Shed Ridge Cap

As Supplied By Others:

- A - 30# (Minimum) Felt with Rosin Paper
- A1 - 40 MIL Ice & Water Shield
- B - Top of Roof Deck or Insulation
- C - Structurals
- D - Trim Boards
- E - #12 x 1" Wafer Head Screws
- E1 - #12 x 1-1/4" Hex Head Screws
- F - Fascia Trim (May be fabricated/supplied by ATAS upon request).
- G - Appropriate anchor screws sufficiently long enough to fully penetrate the solid substrate (Some types/styles available from ATAS.)
- L - Plywood
- U - Butyl Tape Sealant
- V - Support Plate
- WS - Wood Shim 3/8" or 1-3/8"
- * - Indicates color side.

**Field Lock
Shed Ridge Detail
(Fixed)**

Scale: 3" = 1'-0"

		ATAS INTERNATIONAL, INC. Allentown PA 610-395-8445 Mesa AZ 480-558-7210					
TITLE							
FLS Shed Ridge (Fixed) - ply							
DWG NO. / FILE NO.		FLS Shed Ridge (Fixed) - ply				SCALE	3"=1'-0"
DRAWN BY	DAS	DATE	3-6-06	APPR. BY	JEB	DATE	6-1-06
REVISION NO.	XXXX	REVISION DATE	MM/DD/YY	APPR. BY	XXXX	APPR. DATE	MM/DD/YY

Rev. No.	Revision Date	Drawn By	Description of Revision
0	6-1-06	DAS	FLS Shed Ridge (Fixed) - ply