


LOAD TABLES
 .032
 ALUMINUM
 ASTM B209
 3105-H14

DUTCH SEAM ROOF PANEL

MRD110, MRD150, MRD194



L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .032 11" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.379 in.			Yt= 1.344 in.			
S= 0.068 cubic in./ft. (bend.)			S= 0.078 cubic in./ft. (bend.)			
I= 0.095 in. ⁴ /ft. (defl.)			I= 0.090 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 6"	6'- 3"	6'- 5"	6'- 3"	7'- 1"	6'- 11"
15	* 5'- 8"	5'- 1"	5'- 3"	5'- 1"	5'- 10"	5'- 8"
20	5'- 0"	4'- 5"	4'- 7"	4'- 5"	5'- 0"	4'- 11"
25	4'- 6"	3'- 11"	4'- 1"	3'- 11"	4'- 6"	4'- 4"
30	4'- 1"	3'- 7"	3'- 8"	3'- 7"	4'- 1"	4'- 0"
35	3'- 9"	3'- 4"	3'- 5"	3'- 4"	3'- 9"	3'- 8"
40	3'- 6"	3'- 1"	3'- 2"	3'- 1"	3'- 6"	3'- 5"
45	3'- 4"	2'- 11"	3'- 0"	2'- 11"	3'- 4"	3'- 3"
50	3'- 2"	2'- 9"	2'- 10"	2'- 9"	3'- 2"	3'- 1"
55	3'- 0"	2'- 8"	2'- 9"	2'- 8"	3'- 0"	2'- 11"
60	2'- 11"	2'- 6"	2'- 7"	2'- 6"	2'- 11"	2'- 10"
65	2'- 9"	2'- 5"	2'- 6"	2'- 5"	2'- 9"	2'- 8"
70	2'- 8"	2'- 4"	2'- 5"	2'- 4"	2'- 8"	2'- 7"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .032 11" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.379 in.			Yt= 1.344 in.			
S= 0.068 cubic in./ft. (bend.)			S= 0.078 cubic in./ft. (bend.)			
I= 0.095 in. ⁴ /ft. (defl.)			I= 0.090 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 11"	6'- 3"	6'- 5"	* 5'- 10"	7'- 1"	6'- 11"
15	* 5'- 2"	5'- 1"	5'- 3"	* 5'- 1"	5'- 10"	5'- 8"
20	* 4'- 8"	4'- 5"	4'- 7"	4'- 5"	5'- 0"	4'- 11"
25	* 4'- 4"	3'- 11"	4'- 1"	3'- 11"	4'- 6"	4'- 4"
30	* 4'- 1"	3'- 7"	3'- 8"	3'- 7"	4'- 1"	4'- 0"
35	3'- 9"	3'- 4"	3'- 5"	3'- 4"	3'- 9"	3'- 8"
40	3'- 6"	3'- 1"	3'- 2"	3'- 1"	3'- 6"	3'- 5"
45	3'- 4"	2'- 11"	3'- 0"	2'- 11"	3'- 4"	3'- 3"
50	3'- 2"	2'- 9"	2'- 10"	2'- 9"	3'- 2"	3'- 1"
55	3'- 0"	2'- 8"	2'- 9"	2'- 8"	3'- 0"	2'- 11"
60	2'- 11"	2'- 6"	2'- 7"	2'- 6"	2'- 11"	2'- 10"
65	2'- 9"	2'- 5"	2'- 6"	2'- 5"	2'- 9"	2'- 8"
70	2'- 8"	2'- 4"	2'- 5"	2'- 4"	2'- 8"	2'- 7"


L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .032 15" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.422 in.			Yt= 1.392 in.			
S= 0.051 cubic in./ft. (bend.)			S= 0.059 cubic in./ft. (bend.)			
I= 0.073 in. ⁴ /ft. (defl.)			I= 0.069 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 11"	5'- 3"	5'- 6"	5'- 3"	6'- 2"	5'- 10"
15	5'- 0"	4'- 4"	4'- 5"	4'- 4"	5'- 0"	4'- 9"
20	4'- 4"	3'- 9"	3'- 10"	3'- 9"	4'- 4"	4'- 2"
25	3'- 10"	3'- 4"	3'- 5"	3'- 4"	3'- 10"	3'- 8"
30	3'- 6"	3'- 0"	3'- 2"	3'- 0"	3'- 6"	3'- 4"
35	3'- 3"	2'- 10"	2'- 11"	2'- 10"	3'- 3"	3'- 1"
40	3'- 1"	2'- 7"	2'- 9"	2'- 7"	3'- 1"	2'- 11"
45	2'- 10"	2'- 6"	2'- 7"	2'- 6"	2'- 10"	2'- 9"
50	2'- 9"	2'- 4"	2'- 5"	2'- 4"	2'- 9"	2'- 7"
55	2'- 7"	2'- 3"	2'- 4"	2'- 3"	2'- 7"	2'- 6"
60	2'- 6"	2'- 2"	2'- 2"	2'- 2"	2'- 6"	2'- 4"
65	2'- 5"	2'- 1"	2'- 1"	2'- 1"	2'- 5"	2'- 3"
70	2'- 4"	2'- 0"	2'- 0"	2'- 0"	2'- 4"	2'- 2"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .032 15" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.422 in.			Yt= 1.392 in.			
S= 0.051 cubic in./ft. (bend.)			S= 0.059 cubic in./ft. (bend.)			
I= 0.073 in. ⁴ /ft. (defl.)			I= 0.069 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 5"	5'- 3"	5'- 6"	5'- 3"	6'- 2"	5'- 10"
15	* 4'- 9"	4'- 4"	4'- 5"	4'- 4"	5'- 0"	4'- 9"
20	* 4'- 3"	3'- 9"	3'- 10"	3'- 9"	4'- 4"	4'- 2"
25	3'- 10"	3'- 4"	3'- 5"	3'- 4"	3'- 10"	3'- 8"
30	3'- 6"	3'- 0"	3'- 2"	3'- 0"	3'- 6"	3'- 4"
35	3'- 3"	2'- 10"	2'- 11"	2'- 10"	3'- 3"	3'- 1"
40	3'- 1"	2'- 7"	2'- 9"	2'- 7"	3'- 1"	2'- 11"
45	2'- 10"	2'- 6"	2'- 7"	2'- 6"	2'- 10"	2'- 9"
50	2'- 9"	2'- 4"	2'- 5"	2'- 4"	2'- 9"	2'- 7"
55	2'- 7"	2'- 3"	2'- 4"	2'- 3"	2'- 7"	2'- 6"
60	2'- 6"	2'- 2"	2'- 2"	2'- 2"	2'- 6"	2'- 4"
65	2'- 5"	2'- 1"	2'- 1"	2'- 1"	2'- 5"	2'- 3"
70	2'- 4"	2'- 0"	2'- 0"	2'- 0"	2'- 4"	2'- 2"

L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .032 19.25" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.451 in.			Yt= 1.425 in.			
S= 0.040 cubic in./ft. (bend.)			S= 0.046 cubic in./ft. (bend.)			
I= 0.059 in. ⁴ /ft. (defl.)			I= 0.055 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	5'- 5"	4'- 8"	4'- 10"	4'- 8"	5'- 5"	5'- 2"
15	4'- 5"	3'- 9"	3'- 11"	3'- 9"	4'- 5"	4'- 2"
20	3'- 10"	3'- 3"	3'- 5"	3'- 3"	3'- 10"	3'- 8"
25	3'- 5"	2'- 11"	3'- 0"	2'- 11"	3'- 5"	3'- 3"
30	3'- 2"	2'- 8"	2'- 9"	2'- 8"	3'- 2"	2'- 11"
35	2'- 11"	2'- 5"	2'- 7"	2'- 5"	2'- 11"	2'- 9"
40	2'- 8"	2'- 4"	2'- 5"	2'- 4"	2'- 8"	2'- 7"
45	2'- 7"	2'- 2"	2'- 3"	2'- 2"	2'- 7"	2'- 5"
50	2'- 5"	2'- 1"	2'- 1"	2'- 1"	2'- 5"	2'- 3"
55	2'- 4"	1'- 11"	2'- 0"	1'- 11"	2'- 4"	2'- 2"
60	2'- 2"	1'- 10"	1'- 11"	1'- 10"	2'- 2"	2'- 1"
65	2'- 1"	1'- 10"	1'- 10"	1'- 10"	2'- 1"	2'- 0"
70	2'- 0"	1'- 9"	1'- 9"	1'- 9"	2'- 0"	1'- 11"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .032 19.25" COVERAGE						
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.451 in.			Yt= 1.425 in.			
S= 0.040 cubic in./ft. (bend.)			S= 0.046 cubic in./ft. (bend.)			
I= 0.059 in. ⁴ /ft. (defl.)			I= 0.055 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 0"	4'- 8"	4'- 10"	4'- 8"	5'- 5"	5'- 2"
15	* 4'- 5"	3'- 9"	3'- 11"	3'- 9"	4'- 5"	4'- 2"
20	3'- 10"	3'- 3"	3'- 5"	3'- 3"	3'- 10"	3'- 8"
25	3'- 5"	2'- 11"	3'- 0"	2'- 11"	3'- 5"	3'- 3"
30	3'- 2"	2'- 8"	2'- 9"	2'- 8"	3'- 2"	2'- 11"
35	2'- 11"	2'- 5"	2'- 7"	2'- 5"	2'- 11"	2'- 9"
40	2'- 8"	2'- 4"	2'- 5"	2'- 4"	2'- 8"	2'- 7"
45	2'- 7"	2'- 2"	2'- 3"	2'- 2"	2'- 7"	2'- 5"
50	2'- 5"	2'- 1"	2'- 1"	2'- 1"	2'- 5"	2'- 3"
55	2'- 4"	1'- 11"	2'- 0"	1'- 11"	2'- 4"	2'- 2"
60	2'- 2"	1'- 10"	1'- 11"	1'- 10"	2'- 2"	2'- 1"
65	2'- 1"	1'- 10"	1'- 10"	1'- 10"	2'- 1"	2'- 0"
70	2'- 0"	1'- 9"	1'- 9"	1'- 9"	2'- 0"	1'- 11"


- Notes:**
- *Indicates maximum span controlled by deflection.
 - All loads are applied perpendicular to surface of panel.
 - No increase for wind loading has been assumed.
 - Shaded area denotes loads at which deflection of the panel in the transverse direction due to static gravity load may cause permanent deformations.
 - Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified to assess these effects.



LOAD TABLES
.040
ALUMINUM
ASTM B209
3105-H14

DUTCH SEAM ROOF PANEL

MRD110, MRD150, MRD194



L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .040 11" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 7'- 0"	7'- 8"	7'- 11"	* 7'- 0"	8'- 0"	8'- 3"
15	* 6'- 2"	6'- 3"	6'- 6"	* 6'- 1"	6'- 6"	6'- 9"
20	* 5'- 7"	5'- 5"	5'- 7"	5'- 5"	5'- 7"	5'- 10"
25	5'- 0"	4'- 10"	5'- 0"	4'- 10"	5'- 0"	5'- 2"
30	4'- 7"	4'- 5"	4'- 7"	4'- 5"	4'- 7"	4'- 9"
35	4'- 3"	4'- 1"	4'- 3"	4'- 1"	4'- 3"	4'- 5"
40	4'- 0"	3'- 10"	3'- 11"	3'- 10"	4'- 0"	4'- 1"
45	3'- 9"	3'- 7"	3'- 9"	3'- 7"	3'- 9"	3'- 10"
50	3'- 6"	3'- 5"	3'- 6"	3'- 5"	3'- 6"	3'- 8"
55	3'- 4"	3'- 3"	3'- 4"	3'- 3"	3'- 4"	3'- 6"
60	3'- 3"	3'- 1"	3'- 3"	3'- 1"	3'- 3"	3'- 4"
65	3'- 1"	3'- 0"	3'- 1"	3'- 0"	3'- 1"	3'- 2"
70	3'- 0"	2'- 11"	3'- 0"	2'- 11"	3'- 0"	3'- 1"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .040 11" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 5"	7'- 8"	* 7'- 11"	* 6'- 4"	8'- 0"	* 7'- 10"
15	* 5'- 7"	6'- 3"	6'- 6"	* 5'- 6"	6'- 6"	6'- 9"
20	* 5'- 1"	5'- 5"	5'- 7"	* 5'- 0"	5'- 7"	5'- 10"
25	* 4'- 8"	4'- 10"	5'- 0"	* 4'- 8"	5'- 0"	5'- 2"
30	* 4'- 5"	4'- 5"	4'- 7"	* 4'- 5"	4'- 7"	4'- 9"
35	* 4'- 2"	4'- 1"	4'- 3"	4'- 1"	4'- 3"	4'- 5"
40	4'- 0"	3'- 10"	3'- 11"	3'- 10"	4'- 0"	4'- 1"
45	3'- 9"	3'- 7"	3'- 9"	3'- 9"	3'- 7"	3'- 10"
50	3'- 6"	3'- 5"	3'- 6"	3'- 6"	3'- 5"	3'- 8"
55	3'- 4"	3'- 3"	3'- 4"	3'- 4"	3'- 3"	3'- 6"
60	3'- 3"	3'- 1"	3'- 3"	3'- 3"	3'- 1"	3'- 4"
65	3'- 1"	3'- 0"	3'- 1"	3'- 0"	3'- 1"	3'- 2"
70	3'- 0"	2'- 11"	3'- 0"	2'- 11"	3'- 0"	3'- 1"


L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .040 15" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 5"	6'- 6"	6'- 9"	* 6'- 4"	6'- 10"	7'- 1"
15	5'- 7"	5'- 4"	5'- 6"	5'- 4"	5'- 7"	5'- 10"
20	4'- 10"	4'- 7"	4'- 9"	4'- 7"	4'- 10"	5'- 0"
25	4'- 4"	4'- 1"	4'- 3"	4'- 1"	4'- 4"	4'- 6"
30	3'- 11"	3'- 9"	3'- 11"	3'- 9"	3'- 11"	4'- 1"
35	3'- 8"	3'- 6"	3'- 7"	3'- 6"	3'- 8"	3'- 9"
40	3'- 5"	3'- 3"	3'- 4"	3'- 3"	3'- 5"	3'- 6"
45	3'- 3"	3'- 1"	3'- 2"	3'- 1"	3'- 3"	3'- 4"
50	3'- 1"	2'- 11"	3'- 0"	2'- 11"	3'- 1"	3'- 2"
55	2'- 11"	2'- 9"	2'- 10"	2'- 9"	2'- 11"	3'- 0"
60	2'- 9"	2'- 8"	2'- 9"	2'- 8"	2'- 9"	2'- 11"
65	2'- 8"	2'- 6"	2'- 7"	2'- 6"	2'- 8"	2'- 9"
70	2'- 7"	2'- 5"	2'- 6"	2'- 5"	2'- 7"	2'- 8"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .040 15" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 10"	6'- 6"	6'- 9"	* 5'- 9"	6'- 10"	7'- 1"
15	* 5'- 1"	5'- 4"	5'- 6"	* 5'- 1"	5'- 7"	5'- 10"
20	* 4'- 7"	4'- 7"	4'- 9"	* 4'- 7"	4'- 10"	5'- 0"
25	* 4'- 3"	4'- 1"	4'- 3"	4'- 3"	4'- 4"	4'- 6"
30	3'- 11"	3'- 9"	3'- 11"	3'- 9"	3'- 11"	4'- 1"
35	3'- 8"	3'- 6"	3'- 7"	3'- 6"	3'- 8"	3'- 9"
40	3'- 5"	3'- 3"	3'- 4"	3'- 3"	3'- 5"	3'- 6"
45	3'- 3"	3'- 1"	3'- 2"	3'- 1"	3'- 3"	3'- 4"
50	3'- 1"	2'- 11"	3'- 0"	2'- 11"	3'- 1"	3'- 2"
55	2'- 11"	2'- 9"	2'- 10"	2'- 9"	2'- 11"	3'- 0"
60	2'- 9"	2'- 8"	2'- 9"	2'- 8"	2'- 9"	2'- 11"
65	2'- 8"	2'- 6"	2'- 7"	2'- 6"	2'- 8"	2'- 9"
70	2'- 7"	2'- 5"	2'- 6"	2'- 5"	2'- 7"	2'- 8"

L/180 MAXIMUM DEFLECTION CRITERIA GAUGE .040 19.25" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 0"	5'- 9"	5'- 11"	5'- 9"	6'- 1"	6'- 4"
15	5'- 0"	4'- 8"	4'- 10"	4'- 8"	5'- 0"	5'- 2"
20	4'- 3"	4'- 0"	4'- 2"	4'- 0"	4'- 3"	4'- 5"
25	3'- 10"	3'- 7"	3'- 9"	3'- 7"	3'- 10"	4'- 0"
30	3'- 6"	3'- 3"	3'- 5"	3'- 3"	3'- 6"	3'- 7"
35	3'- 3"	3'- 0"	3'- 2"	3'- 0"	3'- 3"	3'- 4"
40	3'- 0"	2'- 10"	2'- 11"	2'- 10"	3'- 0"	3'- 2"
45	2'- 10"	2'- 8"	2'- 9"	2'- 8"	2'- 10"	2'- 11"
50	2'- 8"	2'- 6"	2'- 8"	2'- 6"	2'- 8"	2'- 10"
55	2'- 7"	2'- 5"	2'- 6"	2'- 5"	2'- 7"	2'- 8"
60	2'- 6"	2'- 4"	2'- 5"	2'- 4"	2'- 6"	2'- 7"
65	2'- 4"	2'- 3"	2'- 4"	2'- 3"	2'- 4"	2'- 5"
70	2'- 3"	2'- 2"	2'- 3"	2'- 2"	2'- 3"	2'- 4"

L/240 MAXIMUM DEFLECTION CRITERIA GAUGE .040 19.25" COVERAGE						
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 5'- 5"	5'- 9"	5'- 11"	* 5'- 4"	6'- 1"	6'- 4"
15	* 4'- 9"	4'- 8"	4'- 10"	4'- 8"	5'- 0"	5'- 2"
20	* 4'- 3"	4'- 0"	4'- 2"	4'- 0"	4'- 3"	4'- 5"
25	3'- 10"	3'- 7"	3'- 9"	3'- 7"	3'- 10"	4'- 0"
30	3'- 6"	3'- 3"	3'- 5"	3'- 3"	3'- 6"	3'- 7"
35	3'- 3"	3'- 0"	3'- 2"	3'- 0"	3'- 3"	3'- 4"
40	3'- 0"	2'- 10"	2'- 11"	2'- 10"	3'- 0"	3'- 2"
45	2'- 10"	2'- 8"	2'- 9"	2'- 8"	2'- 10"	2'- 11"
50	2'- 8"	2'- 6"	2'- 8"	2'- 6"	2'- 8"	2'- 10"
55	2'- 7"	2'- 5"	2'- 6"	2'- 5"	2'- 7"	2'- 8"
60	2'- 6"	2'- 4"	2'- 5"	2'- 4"	2'- 6"	2'- 7"
65	2'- 4"	2'- 3"	2'- 4"	2'- 3"	2'- 4"	2'- 5"
70	2'- 3"	2'- 2"	2'- 3"	2'- 2"	2'- 3"	2'- 4"

- Notes:**
- *Indicates maximum span controlled by deflection.
 - All loads are applied perpendicular to surface of panel.
 - No increase for wind loading has been assumed.
 - Shaded area denotes loads at which deflection of the panel in the transverse direction due to static gravity load may cause permanent deformations.
 - Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified to assess these effects.




LOAD TABLES

22 ga. STEEL
ASTM A653
SS 40

DUTCH SEAM ROOF PANEL

MRD110, MRD150, MRD194



L/180 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			11" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.344 in.			Yt= 1.018 in.			
S= 0.070 cubic in/ft. (bend.)			S= 0.055 cubic in/ft. (bend.)			
I= 0.095 in.^4/ft. (defl.)			I= 0.057 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 9'- 4"	9'- 4"	10'- 6"	* 7'- 10"	10'- 6"	* 9'- 9"
15	* 8'- 2"	7'- 8"	8'- 7"	* 6'- 10"	8'- 7"	* 8'- 6"
20	* 7'- 5"	6'- 7"	7'- 5"	* 6'- 3"	7'- 5"	* 7'- 9"
25	6'- 8"	5'- 11"	6'- 7"	* 5'- 9"	6'- 8"	* 7'- 2"
30	6'- 1"	5'- 5"	6'- 0"	5'- 5"	6'- 1"	6'- 7"
35	5'- 7"	5'- 0"	5'- 7"	5'- 0"	5'- 7"	6'- 1"
40	5'- 3"	4'- 8"	5'- 3"	4'- 8"	5'- 3"	5'- 9"
45	4'- 11"	4'- 5"	4'- 11"	4'- 5"	4'- 11"	5'- 5"
50	4'- 8"	4'- 2"	4'- 8"	4'- 2"	4'- 8"	5'- 1"
55	4'- 5"	4'- 0"	4'- 5"	4'- 0"	4'- 5"	4'- 11"
60	4'- 3"	3'- 10"	4'- 3"	3'- 10"	4'- 3"	4'- 8"
65	4'- 1"	3'- 8"	4'- 1"	3'- 8"	4'- 1"	4'- 6"
70	3'- 11"	3'- 6"	3'- 11"	3'- 6"	3'- 11"	4'- 4"

L/240 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			11" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.344 in.			Yt= 1.018 in.			
S= 0.070 cubic in/ft. (bend.)			S= 0.055 cubic in/ft. (bend.)			
I= 0.095 in.^4/ft. (defl.)			I= 0.057 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 8'- 6"	9'- 4"	10'- 6"	* 7'- 2"	* 9'- 7"	* 8'- 10"
15	* 7'- 5"	7'- 8"	8'- 7"	* 6'- 3"	* 8'- 5"	* 7'- 9"
20	* 6'- 9"	6'- 7"	7'- 5"	* 5'- 8"	7'- 5"	* 7'- 0"
25	* 6'- 3"	5'- 11"	6'- 7"	* 5'- 3"	6'- 8"	* 6'- 6"
30	* 5'- 11"	5'- 5"	6'- 0"	* 4'- 11"	6'- 1"	* 6'- 1"
35	* 5'- 7"	5'- 0"	5'- 7"	* 4'- 8"	5'- 7"	* 5'- 10"
40	5'- 3"	4'- 8"	5'- 3"	* 4'- 6"	5'- 3"	* 5'- 7"
45	4'- 11"	4'- 5"	4'- 11"	* 4'- 4"	4'- 11"	* 5'- 4"
50	4'- 8"	4'- 2"	4'- 8"	* 4'- 2"	4'- 8"	5'- 1"
55	4'- 5"	4'- 0"	4'- 5"	4'- 0"	4'- 5"	4'- 11"
60	4'- 3"	3'- 10"	4'- 3"	3'- 10"	4'- 3"	4'- 8"
65	4'- 1"	3'- 8"	4'- 1"	3'- 8"	4'- 1"	4'- 6"
70	3'- 11"	3'- 6"	3'- 11"	3'- 6"	3'- 11"	4'- 4"


L/180 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			15" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.392 in.			Yt= 1.021 in.			
S= 0.052 cubic in/ft. (bend.)			S= 0.041 cubic in/ft. (bend.)			
I= 0.074 in.^4/ft. (defl.)			I= 0.042 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 8'- 7"	8'- 0"	9'- 0"	* 7'- 1"	9'- 1"	* 8'- 9"
15	7'- 5"	6'- 7"	7'- 4"	* 6'- 2"	7'- 5"	* 7'- 8"
20	6'- 5"	5'- 8"	6'- 4"	* 5'- 7"	6'- 5"	6'- 11"
25	5'- 9"	5'- 1"	5'- 8"	5'- 1"	5'- 9"	6'- 3"
30	5'- 3"	4'- 7"	5'- 2"	4'- 7"	5'- 3"	5'- 8"
35	4'- 10"	4'- 3"	4'- 9"	4'- 3"	4'- 10"	5'- 3"
40	4'- 6"	4'- 0"	4'- 6"	4'- 0"	4'- 6"	4'- 11"
45	4'- 3"	3'- 9"	4'- 3"	3'- 9"	4'- 3"	4'- 7"
50	4'- 1"	3'- 7"	4'- 0"	3'- 7"	4'- 1"	4'- 5"
55	3'- 10"	3'- 5"	3'- 10"	3'- 5"	3'- 10"	4'- 2"
60	3'- 8"	3'- 3"	3'- 8"	3'- 3"	3'- 8"	4'- 0"
65	3'- 6"	3'- 1"	3'- 1"	3'- 1"	3'- 6"	3'- 10"
70	3'- 5"	3'- 0"	3'- 0"	3'- 0"	3'- 5"	3'- 8"

L/240 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			15" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.392 in.			Yt= 1.021 in.			
S= 0.052 cubic in/ft. (bend.)			S= 0.041 cubic in/ft. (bend.)			
I= 0.074 in.^4/ft. (defl.)			I= 0.042 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 7'- 10"	8'- 0"	9'- 0"	* 6'- 5"	* 8'- 8"	* 8'- 0"
15	* 6'- 10"	6'- 7"	7'- 4"	* 5'- 7"	7'- 5"	* 7'- 0"
20	* 6'- 2"	5'- 8"	6'- 4"	* 5'- 1"	6'- 5"	* 6'- 4"
25	5'- 9"	5'- 1"	5'- 8"	* 4'- 9"	5'- 9"	* 5'- 10"
30	5'- 3"	4'- 7"	5'- 2"	* 4'- 5"	5'- 3"	* 5'- 6"
35	4'- 10"	4'- 3"	4'- 9"	* 4'- 3"	4'- 10"	* 5'- 3"
40	4'- 6"	4'- 0"	4'- 6"	4'- 0"	4'- 6"	4'- 11"
45	4'- 3"	3'- 9"	4'- 3"	3'- 9"	4'- 3"	4'- 7"
50	4'- 1"	3'- 7"	4'- 0"	3'- 7"	4'- 1"	4'- 5"
55	3'- 10"	3'- 5"	3'- 10"	3'- 5"	3'- 10"	4'- 2"
60	3'- 8"	3'- 3"	3'- 8"	3'- 3"	3'- 8"	4'- 0"
65	3'- 6"	3'- 1"	3'- 1"	3'- 1"	3'- 6"	3'- 10"
70	3'- 5"	3'- 0"	3'- 0"	3'- 0"	3'- 5"	3'- 8"

L/180 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			19.25" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.425 in.			Yt= 1.022 in.			
S= 0.041 cubic in/ft. (bend.)			S= 0.032 cubic in/ft. (bend.)			
I= 0.059 in.^4/ft. (defl.)			I= 0.032 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 8'- 0"	7'- 1"	7'- 11"	* 6'- 6"	8'- 1"	* 8'- 1"
15	6'- 7"	5'- 9"	6'- 6"	* 5'- 8"	6'- 7"	* 7'- 1"
20	5'- 8"	5'- 0"	5'- 7"	5'- 0"	5'- 8"	6'- 2"
25	5'- 1"	4'- 6"	5'- 0"	4'- 6"	5'- 1"	5'- 6"
30	4'- 8"	4'- 1"	4'- 7"	4'- 1"	4'- 8"	5'- 0"
35	4'- 4"	3'- 9"	4'- 3"	3'- 9"	4'- 4"	4'- 8"
40	4'- 0"	3'- 6"	3'- 11"	3'- 6"	4'- 0"	4'- 4"
45	3'- 9"	3'- 4"	3'- 9"	3'- 4"	3'- 9"	4'- 1"
50	3'- 7"	3'- 2"	3'- 6"	3'- 2"	3'- 7"	3'- 10"
55	3'- 5"	3'- 0"	3'- 4"	3'- 0"	3'- 5"	3'- 8"
60	3'- 3"	2'- 10"	3'- 3"	2'- 10"	3'- 3"	3'- 6"
65	3'- 2"	2'- 9"	3'- 1"	2'- 9"	3'- 2"	3'- 5"
70	3'- 0"	2'- 8"	3'- 0"	2'- 8"	3'- 0"	3'- 3"

L/240 MAXIMUM DEFLECTION CRITERIA						
22 GAUGE			19.25" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.425 in.			Yt= 1.022 in.			
S= 0.041 cubic in/ft. (bend.)			S= 0.032 cubic in/ft. (bend.)			
I= 0.059 in.^4/ft. (defl.)			I= 0.032 in.^4/ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 8'- 0"	7'- 1"	7'- 11"	* 5'- 11"	7'- 1"	* 8'- 4"
15	6'- 7"	5'- 9"	6'- 6"	* 5'- 2"	6'- 7"	* 6'- 5"
20	5'- 8"	5'- 0"	5'- 7"	4'- 8"	5'- 8"	5'- 10"
25	5'- 1"	4'- 6"	5'- 0"	4'- 4"	5'- 1"	5'- 5"
30	4'- 8"	4'- 1"	4'- 7"	4'- 1"	4'- 8"	5'- 0"
35	4'- 4"	3'- 9"	4'- 3"	3'- 9"	4'- 4"	4'- 8"
40	4'- 0"	3'- 6"	3'- 11"	3'- 6"	4'- 0"	4'- 4"
45	3'- 9"	3'- 4"	3'- 9"	3'- 4"	3'- 9"	4'- 1"
50	3'- 7"	3'- 2"	3'- 6"	3'- 2"	3'- 7"	3'- 10"
55	3'- 5"	3'- 0"	3'- 4"	3'- 0"	3'- 5"	3'- 8"
60	3'- 3"	2'- 10"	3'- 3"	2'- 10"	3'- 3"	3'- 6"
65	3'- 2"	2'- 9"	3'- 1"	2'- 9"	3'- 2"	3'- 5"
70	3'- 0"	2'- 8"	3'- 0"	2'- 8"	3'- 0"	3'- 3"

- Notes:**
- *Indicates maximum span controlled by deflection.
 - All loads are applied perpendicular to surface of panel.
 - No increase for wind loading has been assumed.
 - Shaded area denotes loads at which deflection of the panel in the transverse direction due to static gravity load may cause permanent deformations.
 - Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified to assess these effects.




LOAD TABLES

24 ga. STEEL
ASTM A653
SS 40

DUTCH SEAM ROOF PANEL

MRD110, MRD150, MRD194



L/180 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			11" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 8'- 4"	7'- 9"	8'- 8"	* 7'- 0"	9'- 0"	* 8'- 7"
15	* 7'- 3"	6'- 4"	7'- 1"	* 6'- 1"	7'- 4"	* 7'- 6"
20	6'- 4"	5'- 6"	6'- 2"	5'- 6"	6'- 4"	6'- 9"
25	5'- 8"	4'- 11"	5'- 6"	4'- 11"	5'- 8"	6'- 0"
30	5'- 2"	4'- 6"	5'- 0"	4'- 6"	5'- 2"	5'- 6"
35	4'- 10"	4'- 2"	4'- 8"	4'- 2"	4'- 10"	5'- 1"
40	4'- 6"	3'- 10"	4'- 4"	3'- 10"	4'- 6"	4'- 9"
45	4'- 3"	3'- 8"	4'- 1"	3'- 8"	4'- 3"	4'- 6"
50	4'- 0"	3'- 5"	3'- 10"	3'- 5"	4'- 0"	4'- 3"
55	3'- 10"	3'- 3"	3'- 8"	3'- 3"	3'- 10"	4'- 0"
60	3'- 8"	3'- 2"	3'- 6"	3'- 2"	3'- 8"	3'- 10"
65	3'- 6"	3'- 0"	3'- 5"	3'- 0"	3'- 6"	3'- 9"
70	3'- 5"	2'- 11"	3'- 3"	2'- 11"	3'- 5"	3'- 7"

L/240 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			11" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 7'- 7"	7'- 9"	8'- 8"	* 6'- 4"	* 8'- 6"	* 7'- 10"
15	* 6'- 7"	6'- 4"	7'- 1"	* 5'- 6"	7'- 4"	* 6'- 10"
20	* 6'- 0"	5'- 6"	6'- 2"	* 5'- 0"	6'- 4"	* 6'- 2"
25	* 5'- 7"	4'- 11"	5'- 6"	* 4'- 8"	5'- 8"	* 5'- 9"
30	5'- 2"	4'- 6"	5'- 0"	* 4'- 4"	5'- 2"	* 5'- 5"
35	4'- 10"	4'- 2"	4'- 8"	4'- 2"	4'- 10"	5'- 1"
40	4'- 6"	3'- 10"	4'- 4"	3'- 10"	4'- 6"	4'- 9"
45	4'- 3"	3'- 8"	4'- 1"	3'- 8"	4'- 3"	4'- 6"
50	4'- 0"	3'- 5"	3'- 10"	3'- 5"	4'- 0"	4'- 3"
55	3'- 10"	3'- 3"	3'- 8"	3'- 3"	3'- 10"	4'- 0"
60	3'- 8"	3'- 2"	3'- 6"	3'- 2"	3'- 8"	3'- 10"
65	3'- 6"	3'- 0"	3'- 5"	3'- 0"	3'- 6"	3'- 9"
70	3'- 5"	2'- 11"	3'- 3"	2'- 11"	3'- 5"	3'- 7"

L/180 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			15" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 7'- 6"	6'- 8"	7'- 5"	* 6'- 3"	7'- 9"	* 7'- 9"
15	6'- 3"	5'- 5"	6'- 1"	5'- 5"	6'- 3"	6'- 8"
20	5'- 5"	4'- 8"	5'- 3"	4'- 8"	5'- 5"	5'- 9"
25	4'- 10"	4'- 2"	4'- 8"	4'- 2"	4'- 10"	5'- 2"
30	4'- 5"	3'- 10"	4'- 3"	3'- 10"	4'- 5"	4'- 8"
35	4'- 1"	3'- 6"	4'- 0"	3'- 6"	4'- 1"	4'- 4"
40	3'- 10"	3'- 4"	3'- 8"	3'- 4"	3'- 10"	4'- 1"
45	3'- 7"	3'- 1"	3'- 6"	3'- 1"	3'- 7"	3'- 10"
50	3'- 5"	2'- 11"	3'- 4"	2'- 11"	3'- 5"	3'- 7"
55	3'- 3"	2'- 10"	3'- 2"	2'- 10"	3'- 3"	3'- 5"
60	3'- 1"	2'- 8"	3'- 0"	2'- 8"	3'- 1"	3'- 4"
65	3'- 0"	2'- 7"	2'- 11"	2'- 7"	3'- 0"	3'- 2"
70	2'- 11"	2'- 6"	2'- 9"	2'- 6"	2'- 11"	3'- 1"

L/240 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			15" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 10"	6'- 8"	7'- 5"	* 5'- 8"	* 7'- 8"	* 7'- 1"
15	* 5'- 11"	5'- 5"	6'- 1"	* 5'- 0"	6'- 3"	* 6'- 2"
20	* 5'- 5"	4'- 8"	5'- 3"	* 4'- 6"	5'- 5"	* 5'- 7"
25	4'- 10"	4'- 2"	4'- 8"	* 4'- 2"	4'- 10"	5'- 2"
30	4'- 5"	3'- 10"	4'- 3"	3'- 10"	4'- 5"	4'- 8"
35	4'- 1"	3'- 6"	4'- 0"	3'- 6"	4'- 1"	4'- 4"
40	3'- 10"	3'- 4"	3'- 8"	3'- 4"	3'- 10"	4'- 1"
45	3'- 7"	3'- 1"	3'- 6"	3'- 1"	3'- 7"	3'- 10"
50	3'- 5"	2'- 11"	3'- 4"	2'- 11"	3'- 5"	3'- 7"
55	3'- 3"	2'- 10"	3'- 2"	2'- 10"	3'- 3"	3'- 5"
60	3'- 1"	2'- 8"	3'- 0"	2'- 8"	3'- 1"	3'- 4"
65	3'- 0"	2'- 7"	2'- 11"	2'- 7"	3'- 0"	3'- 2"
70	2'- 11"	2'- 6"	2'- 9"	2'- 6"	2'- 11"	3'- 1"

L/180 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			19.25" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	6'- 10"	5'- 10"	6'- 7"	* 5'- 9"	6'- 10"	* 7'- 2"
15	5'- 7"	4'- 9"	5'- 4"	4'- 9"	5'- 7"	5'- 10"
20	4'- 10"	4'- 2"	4'- 8"	4'- 2"	4'- 10"	5'- 1"
25	4'- 3"	3'- 8"	4'- 2"	3'- 8"	4'- 3"	4'- 6"
30	3'- 11"	3'- 4"	3'- 9"	3'- 11"	4'- 2"	4'- 2"
35	3'- 7"	3'- 1"	3'- 6"	3'- 1"	3'- 7"	3'- 10"
40	3'- 5"	2'- 11"	3'- 3"	2'- 11"	3'- 5"	3'- 7"
45	3'- 2"	2'- 9"	3'- 1"	2'- 9"	3'- 2"	3'- 4"
50	3'- 0"	2'- 7"	2'- 11"	2'- 7"	3'- 0"	3'- 2"
55	2'- 11"	2'- 6"	2'- 9"	2'- 6"	2'- 11"	3'- 1"
60	2'- 9"	2'- 4"	2'- 8"	2'- 4"	2'- 9"	2'- 11"
65	2'- 8"	2'- 3"	2'- 7"	2'- 3"	2'- 8"	2'- 10"
70	2'- 7"	2'- 2"	2'- 5"	2'- 2"	2'- 7"	2'- 8"

L/240 MAXIMUM DEFLECTION CRITERIA						
24 GAUGE			19.25" COVERAGE			
POSITIVE BENDING			NEGATIVE BENDING			
Yt= 1.308 in.			Yt= 0.915 in.			
S= 0.047 cubic in/ft. (bend.)			S= 0.035 cubic in/ft. (bend.)			
I= 0.061 in. ⁴ /ft. (defl.)			I= 0.036 in. ⁴ /ft. (defl.)			
LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN
10	* 6'- 3"	5'- 10"	6'- 7"	* 5'- 3"	* 6'- 10"	* 6'- 6"
15	5'- 5"	4'- 9"	5'- 4"	4'- 9"	5'- 7"	5'- 8"
20	4'- 10"	4'- 2"	4'- 8"	4'- 2"	4'- 10"	5'- 1"
25	4'- 3"	3'- 8"	4'- 2"	3'- 8"	4'- 3"	4'- 6"
30	3'- 11"	3'- 4"	3'- 9"	3'- 11"	4'- 2"	4'- 2"
35	3'- 7"	3'- 1"	3'- 6"	3'- 1"	3'- 7"	3'- 10"
40	3'- 5"	2'- 11"	3'- 3"	2'- 11"	3'- 5"	3'- 7"
45	3'- 2"	2'- 9"	3'- 1"	2'- 9"	3'- 2"	3'- 4"
50	3'- 0"	2'- 7"	2'- 11"	2'- 7"	3'- 0"	3'- 2"
55	2'- 11"	2'- 6"	2'- 9"	2'- 6"	2'- 11"	3'- 1"
60	2'- 9"	2'- 4"	2'- 8"	2'- 4"	2'- 9"	2'- 11"
65	2'- 8"	2'- 3"	2'- 7"	2'- 3"	2'- 8"	2'- 10"
70	2'- 7"	2'- 2"	2'- 5"	2'- 2"	2'- 7"	2'- 8"

Notes:

- *Indicates maximum span controlled by deflection.
- All loads are applied perpendicular to surface of panel.
- No increase for wind loading has been assumed.
- Shaded area denotes loads at which deflection of the panel in the transverse direction due to static gravity load may cause permanent deformations.
- Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified to assess these effects.