


LOAD TABLES
0.032 ALUMINUM
ASTM B209
3003-H14
39 3/8" COVERAGE

INSPIRE WALL PANEL BWS390



FTY=17KSI		
	0.032	
	Top in Compression	Bottom in Compression
Yt=	0.4243 in	0.4243 in
Yb=	0.8257 in	0.8257 in
St=	0.2554 in ³ /ft	0.2554 in ³ /ft
Sb=	0.1313 in ³ /ft	0.1313 in ³ /ft
I=	0.1084 in ⁴ /ft	0.1084 in ⁴ /ft
M _a =	0.0823 ft-k/ft	0.0742 ft-k/ft
P _{c,int} =	296 lb/ft	296 lb/ft
P _{c,end} =	128 lb/ft	128 lb/ft

Load (psf)	Δ ≤ L/240 Deflection Criteria			Δ ≤ L/180 Deflection Criteria			Δ ≤ L/120 Deflection Criteria		
	Span Condition			Span Condition			Span Condition		
	Single	Double	Triple	Single	Double	Triple	Single	Double	Triple
10	*6'-2"	7'-2"	*7'-8"	*6'-10"	7'-2"	8'-1"	*7'-10"	7'-2"	8'-1"
15	*5'-5"	5'-9"	6'-5"	*6'-0"	5'-9"	6'-5"	6'-7"	5'-9"	6'-5"
20	*4'-11"	4'-10"	5'-6"	*5'-5"	4'-10"	5'-6"	5'-8"	4'-10"	5'-6"
25	*4'-7"	4'-3"	4'-10"	*5'-0"	4'-3"	4'-10"	5'-1"	4'-3"	4'-10"
30	*4'-3"	3'-10"	4'-4"	4'-8"	3'-10"	4'-4"	4'-8"	3'-10"	4'-4"
35	*4'-1"	3'-6"	3'-11"	4'-4"	3'-6"	3'-11"	4'-4"	3'-6"	3'-11"
40	*3'-11"	3'-2"	3'-7"	4'-0"	3'-2"	3'-7"	4'-0"	3'-2"	3'-7"
45	*3'-9"	3'-0"	3'-4"	3'-9"	3'-0"	3'-4"	3'-9"	3'-0"	3'-4"
50	3'-7"	2'-9"	3'-1"	3'-7"	2'-9"	3'-1"	3'-7"	2'-9"	3'-1"
55	3'-5"	2'-7"	2'-11"	3'-5"	2'-7"	2'-11"	3'-5"	2'-7"	2'-11"
60	3'-3"	2'-5"	2'-9"	3'-3"	2'-5"	2'-9"	3'-3"	2'-5"	2'-9"
65	3'-2"	2'-4"	2'-7"	3'-2"	2'-4"	2'-7"	3'-2"	2'-4"	2'-7"
70	3'-0"	2'-2"	2'-6"	3'-0"	2'-2"	2'-6"	3'-0"	2'-2"	2'-6"
75	2'-11"	2'-1"	2'-4"	2'-11"	2'-1"	2'-4"	2'-11"	2'-1"	2'-4"
80	2'-10"	2'-0"	2'-3"	2'-10"	2'-0"	2'-3"	2'-10"	2'-0"	2'-3"
85	2'-9"	1'-11"	2'-2"	2'-9"	1'-11"	2'-2"	2'-9"	1'-11"	2'-2"
90	2'-8"	1'-10"	2'-1"	2'-8"	1'-10"	2'-1"	2'-8"	1'-10"	2'-1"
95	2'-7"	1'-9"	2'-0"	2'-7"	1'-9"	2'-0"	2'-7"	1'-9"	2'-0"
100	2'-6"	1'-8"	1'-11"	2'-6"	1'-8"	1'-11"	2'-6"	1'-8"	1'-11"

Load (psf)	Δ ≤ L/240 Deflection Criteria			Δ ≤ L/180 Deflection Criteria			Δ ≤ L/120 Deflection Criteria		
	Span Condition			Span Condition			Span Condition		
	Single	Double	Triple	Single	Double	Triple	Single	Double	Triple
10	*6'-2"	7'-7"	*7'-8"	*6'-10"	7'-7"	8'-5"	7'-8"	7'-7"	8'-5"
15	*5'-5"	6'-0"	*6'-8"	*6'-0"	6'-0"	6'-9"	6'-3"	6'-0"	6'-9"
20	*4'-11"	5'-1"	5'-8"	5'-5"	5'-1"	5'-8"	5'-5"	5'-1"	5'-8"
25	*4'-7"	4'-5"	5'-0"	4'-10"	4'-5"	5'-0"	4'-10"	4'-5"	5'-0"
30	*4'-3"	4'-0"	4'-6"	4'-5"	4'-0"	4'-6"	4'-5"	4'-0"	4'-6"
35	4'-1"	3'-7"	4'-1"	4'-1"	3'-7"	4'-1"	4'-1"	3'-7"	4'-1"
40	3'-10"	3'-4"	3'-9"	3'-10"	3'-4"	3'-9"	3'-10"	3'-4"	3'-9"
45	3'-7"	3'-1"	3'-6"	3'-7"	3'-1"	3'-6"	3'-7"	3'-1"	3'-6"
50	3'-5"	2'-10"	3'-3"	3'-5"	2'-10"	3'-3"	3'-5"	2'-10"	3'-3"
55	3'-3"	2'-8"	3'-0"	3'-3"	2'-8"	3'-0"	3'-3"	2'-8"	3'-0"
60	3'-1"	2'-6"	2'-10"	3'-1"	2'-6"	2'-10"	3'-1"	2'-6"	2'-10"
65	3'-0"	2'-5"	2'-8"	3'-0"	2'-5"	2'-8"	3'-0"	2'-5"	2'-8"
70	2'-10"	2'-3"	2'-7"	2'-10"	2'-3"	2'-7"	2'-10"	2'-3"	2'-7"
75	2'-9"	2'-2"	2'-5"	2'-9"	2'-2"	2'-5"	2'-9"	2'-2"	2'-5"
80	2'-8"	2'-1"	2'-4"	2'-8"	2'-1"	2'-4"	2'-8"	2'-1"	2'-4"
85	2'-7"	2'-0"	2'-3"	2'-7"	2'-0"	2'-3"	2'-7"	2'-0"	2'-3"
90	2'-6"	1'-11"	2'-2"	2'-6"	1'-11"	2'-2"	2'-6"	1'-11"	2'-2"
95	2'-5"	1'-10"	2'-1"	2'-5"	1'-10"	2'-1"	2'-5"	1'-10"	2'-1"
100	2'-5"	1'-9"	2'-0"	2'-5"	1'-9"	2'-0"	2'-5"	1'-9"	2'-0"

- Notes:
1. Minimum 1.5" bearing assumed.
 2. Connection of panel to supporting structure not investigated.
 3. Design thickness assumed 0.002" less than nominal thickness.
 4. Span lengths indicated by * are controlled by deflection.
 5. These load tables conform to the 2005 edition of the "Aluminum Design Manual."
 6. Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified to assess these effects.
 7. Load tables are based upon section property analysis. Other factors such as fastener adequacy may apply to allowable span conditions per project.