



Quantity:

- ____ Total LF (12'-0" pcs)
- ____ Radius Fascia LF (6'-0" pcs) (Radius: _____, Convex or Concave)
- ____ Vaulted Fascia LF (6'-0" pcs) (Radius: _____, Convex or Concave)

Standard Accessories:

- ____ Inside Mitered Corner(s) (Angle: _____)
- ____ Outside Mitered Corner(s) (Angle: _____)

Custom Accessories: (sketches required)

Special Miters and Zees

*All Components for installing Accessories are included.

MATERIAL:

THICKNESS:

- Pre-Finished Aluminum .040 .050 .063
- Mill Finished Aluminum .040 .050 .063
- Pre-Finished Steel 24 ga 22 ga
- Stainless Steel 24 ga 22 ga

COLOR: _____

-	C DIMENSION	H DIMENSION
-	2-1/2"	3-1/4"
-	4"	4-3/4"
-	5-1/2"	6-1/4"
-	7"	7-3/4"

ANSI/SPRI ES-1 Tested

Projects Requirement's
Horizontal Design Pressure: _____ psf

Job Name:	Customer:
Job #:	Representative:
Location:	Distributor:

CUSTOMER APPROVAL

Authorized Signature: _____

Approved by: _____

Date: _____