

LOAD TABLES


ALUMINUM

ASTM B209

3003-H16

12" COVERAGE

METAFOR WALL PANEL MFP120



L/60 MAXIMUM DEFLECTION CRITERIA GAUGE .032

AREA:	0.51216 in ² /ft.	Sb:	0.11112 in ³ /ft.
Yb:	0.26321 in.	St:	0.10983 in ³ /ft.
Yt:	0.26629 in.	I:	0.02925 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD						
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN				
10	6'- 4"	*	7'- 6"	7'- 10"	6'- 4"	*	7'- 5"	7'- 10"		
15	5'- 6"	*	6'- 1"	*	6'- 10"	5'- 6"	*	6'- 1"	*	6'- 10"
20	5'- 0"	*	5'- 3"	*	5'- 11"	5'- 0"	*	5'- 3"	*	5'- 11"
25	4'- 8"	*	4'- 9"	*	5'- 3"	4'- 8"	*	5'- 3"	*	5'- 3"
30	*	4'- 3"	*	4'- 4"	*	4'- 10"	*	4'- 4"	*	4'- 10"
35	*	4'- 0"	*	4'- 0"	*	4'- 0"	*	4'- 0"	*	4'- 5"
40	*	3'- 8"	*	3'- 9"	*	3'- 8"	*	4'- 2"	*	4'- 2"
45	*	3'- 6"	*	3'- 6"	*	3'- 6"	*	3'- 11"	*	3'- 11"
50	*	3'- 4"	*	3'- 4"	*	3'- 4"	*	3'- 8"	*	3'- 8"
55	*	3'- 2"	*	3'- 2"	*	3'- 7"	*	3'- 2"	*	3'- 6"
60	*	3'- 0"	*	3'- 0"	*	3'- 0"	*	3'- 5"	*	3'- 5"
65	*	2'- 11"	*	2'- 11"	*	2'- 11"	*	3'- 3"	*	3'- 3"
70	*	2'- 10"	*	2'- 10"	*	2'- 10"	*	3'- 2"	*	3'- 2"

L/60 MAXIMUM DEFLECTION CRITERIA GAUGE .040

AREA:	0.64156 in ² /ft.	Sb:	0.13734 in ³ /ft.
Yb:	0.25929 in.	St:	0.13581 in ³ /ft.
Yt:	0.26221 in.	I:	0.03561 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD						
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN				
10	6'- 9"	*	9'- 1"	8'- 5"	6'- 9"	*	9'- 1"	8'- 5"		
15	5'- 11"	*	7'- 5"	7'- 4"	5'- 11"	*	7'- 5"	7'- 4"		
20	5'- 4"	*	6'- 5"	6'- 8"	5'- 4"	*	6'- 5"	6'- 8"		
25	5'- 0"	*	5'- 9"	6'- 2"	5'- 0"	*	5'- 9"	6'- 2"		
30	4'- 8"	*	5'- 3"	5'- 10"	4'- 8"	*	5'- 3"	5'- 10"		
35	4'- 5"	*	4'- 10"	*	5'- 5"	4'- 5"	*	4'- 10"	*	5'- 5"
40	4'- 3"	*	4'- 6"	*	5'- 1"	4'- 3"	*	4'- 6"	*	5'- 1"
45	4'- 1"	*	4'- 3"	*	4'- 9"	4'- 1"	*	4'- 3"	*	4'- 9"
50	3'- 11"	*	4'- 1"	*	4'- 6"	3'- 11"	*	4'- 0"	*	4'- 6"
55	3'- 10"	*	3'- 10"	*	4'- 4"	3'- 10"	*	4'- 4"	*	4'- 4"
60	*	3'- 8"	*	3'- 8"	*	3'- 2"	*	3'- 8"	*	3'- 1"
65	*	3'- 6"	*	3'- 7"	*	3'- 6"	*	3'- 11"	*	3'- 6"
70	*	3'- 5"	*	3'- 10"	*	3'- 5"	*	3'- 10"	*	3'- 5"

L/60 MAXIMUM DEFLECTION CRITERIA GAUGE .050

AREA:	0.80044 in ² /ft.	Sb:	0.16849 in ³ /ft.
Yb:	0.25440 in.	St:	0.16672 in ³ /ft.
Yt:	0.25710 in.	I:	0.04286 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD						
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN				
10	7'- 2"	*	9'- 8"	8'- 11"	7'- 2"	*	9'- 8"	8'- 11"		
15	6'- 3"	*	8'- 5"	7'- 9"	6'- 3"	*	8'- 5"	7'- 9"		
20	5'- 9"	*	7'- 7"	7'- 1"	5'- 9"	*	7'- 6"	7'- 1"		
25	5'- 4"	*	6'- 9"	6'- 7"	5'- 4"	*	6'- 9"	6'- 7"		
30	5'- 0"	*	6'- 2"	6'- 2"	5'- 0"	*	6'- 2"	6'- 2"		
35	4'- 9"	*	5'- 9"	5'- 10"	4'- 9"	*	5'- 8"	5'- 10"		
40	4'- 6"	*	5'- 4"	5'- 7"	4'- 6"	*	5'- 4"	5'- 7"		
45	4'- 4"	*	5'- 0"	5'- 5"	4'- 4"	*	5'- 0"	5'- 5"		
50	4'- 2"	*	4'- 9"	5'- 2"	4'- 2"	*	4'- 9"	5'- 2"		
55	4'- 1"	*	4'- 7"	5'- 0"	4'- 1"	*	4'- 6"	5'- 0"		
60	3'- 11"	*	4'- 4"	*	4'- 11"	3'- 11"	*	4'- 4"	*	4'- 11"
65	3'- 10"	*	4'- 2"	*	4'- 8"	3'- 10"	*	4'- 2"	*	4'- 10"
70	3'- 9"	*	4'- 0"	*	4'- 6"	3'- 9"	*	4'- 0"	*	4'- 8"

- Notes:
- *Indicates that maximum span length is controlled by stress.
 - All loads are applied perpendicular to surface of panel.
 - All computations have been made in accordance with the Aluminum Association's Specifications for Aluminum Structures.
 - Since allowable loads and spans can be affected by actual conditions of use, information in these tables is intended for use only by those qualified

L/120 MAXIMUM DEFLECTION CRITERIA GAUGE .032

AREA:	0.51216 in ² /ft.	Sb:	0.11112 in ³ /ft.
Yb:	0.26321 in.	St:	0.10983 in ³ /ft.
Yt:	0.26629 in.	I:	0.02925 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN

L/120 MAXIMUM DEFLECTION CRITERIA GAUGE .040

AREA:	0.64156 in ² /ft.	Sb:	0.13734 in ³ /ft.
Yb:	0.25929 in.	St:	0.13581 in ³ /ft.
Yt:	0.26221 in.	I:	0.03561 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN

L/120 MAXIMUM DEFLECTION CRITERIA GAUGE .050

AREA:	0.80044 in ² /ft.	Sb:	0.16849 in ³ /ft.
Yb:	0.25440 in.	St:	0.16672 in ³ /ft.
Yt:	0.25710 in.	I:	0.04286 in ⁴ /ft.

LOAD (PSF)	DOWNWARD LOAD			UPWARD LOAD		
	SINGLE SPAN	DOUBLE SPAN	THREE SPAN	SINGLE SPAN	DOUBLE SPAN	THREE SPAN

- to assess these effects.
5. Spans for nominal 0.032", 0.040" and 0.050" aluminum were determined at an actual thickness of 0.0305", 0.0385" and 0.0485", respectively.
6. Load tables are based upon section property analysis. Other factors such as fastener adequacy may apply to allowable span conditions per project.