



**Product Approval**  
USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

OFFICE OF THE SECRETARY

FL #	FL20821-R3
Application Type	Revision
Code Version	2023
Application Status	Approved
	*Approved by DBPR. Approvals by DBPR shall be reviewed and ratified by the POC and/or the Commission if necessary.
Comments	
Archived	<input type="checkbox"/>
Product Manufacturer	ATAS International, Inc.
Address/Phone/Email	6612 Snowdrift Road Allentown, PA 18106 (610) 395-8445 Ext 223 jbush@atas.com
Authorized Signature	james bush jbush@atas.com
Technical Representative	James E. Bush
Address/Phone/Email	ATAS International, Inc. 6612 Snowdrift Road Allentown, PA 18106 jbush@atas.com
Quality Assurance Representative	James Bush
Address/Phone/Email	6612 Snowdrift Road Allentown, PA 18106 jbush@atas.com
Category	Roofing
Subcategory	Roofing Accessories that are an Integral Part of the Roofing System
Compliance Method	Test Report
Testing Lab	Architectural Testing, Inc. (an Intertek company) - York, PA
Quality Assurance Entity	Intertek Testing Services NA, Inc. - QA Entity
Quality Assurance Contract Expiration Date	12/31/2026
Validated By	Steven M. Urich, PE <input checked="" type="checkbox"/> Validation Checklist - Hardcopy Received
Certificate of Independence	<a href="#">FL20821_R3_COI_ati_letter_of_ind.pdf</a>
Referenced Standard and Year (of Standard)	<b>Standard</b> ANSI/SPRI/FM 4435/ES-1
	<b>Year</b> 2017
Equivalence of Product Standards	
Certified By	Approved Testing Lab <a href="#">FL20821_R3_Equiv_Equivalency_Letter - R1.pdf</a>
Product Approval Method	Method 1 Option B
Date Submitted	02/19/2024
Date Validated	03/07/2024
Date Pending FBC Approval	
Date Approved	03/09/2024

**Summary of Products**

FL #	Model, Number or Name	Description
20821.1	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 10" wide. 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 229 psf and rated upward 397 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Continuous Cleat Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.2	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 10" wide. .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 231 psf and rated upward 400 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Continuous Cleat Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.3	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" back face height, 24 wide. .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 98 psf and rated upward 170 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Continuous Cleat Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.4	Continuous Cleat Coping	5 1/2" front face height, 4 1/2" rear face height, 24" wide. .24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 90 psf and rated upward 157 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Continuous Cleat Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.5	Drip Edge Fascia	7 3/4" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 243 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Drip Edge Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.6	Drip Edge Fascia	7 3/4" face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 230 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Drip Edge Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.7	Edge-Lok 2 Fascia	11 3/4" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 50 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Edge Lok 2 Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.8	Edge-Lok 2 Fascia	11 3/4" face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 40 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Edge Lok 2 Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.9	Edge-Lok 3 Fascia	11 3/4" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 133 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Edge Lok 3 - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.10	Edge-Lok 3 Fascia	11 3/4" face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Edge Lok 3 Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA

<b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 140 psf		<b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.11	Gravel Stop	8 1/2" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 203 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Gravel Stop Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.12	Gravel Stop	8 1/2" face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 200 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Gravel Stop Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.13	Rapid-Lok Coping	7 1/2 front face height, 5 1/2 back face height, 12 3/4" wide. 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 60 psf and rated upward 103 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.14	Rapid-Lok Coping	7 1/2: front face height, 5 1/2" back face height, 12 3/4" wide. .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 67 psf and rated upward 117 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.15	Rapid-Lok Coping	7 1/2" front face height, 5 1/2" back face heath, 32" wide. 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 25 psi and rated upward 43 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.16	Rapid-Lok Coping	7 1/2" front face, 5 1/2" back face, 32" wide. .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 29 psf and rated upward 50 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Coping - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.17	Rapid-Lok Fascia	5 1/2 face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 593 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.18	Rapid-Lok Fascia	11 1/2" face height, 24 ga. steel
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 133 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.02-119-16-r0 (2).pdf</a>
20821.19	Rapid-Lok Fascia	5 1/2" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A <b>Design Pressure:</b> N/A <b>Other:</b> Rated outward 490 psf		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA <b>Test Reports</b> <a href="#">FL20821_R3_TR_f1420.01-119-16-r1.pdf</a>
20821.20	Rapid-Lok Fascia	11 1/2" face height, .040 aluminum
<b>Limits of Use</b> <b>Approved for use in HVHZ:</b> Yes <b>Approved for use outside HVHZ:</b> Yes <b>Impact Resistant:</b> N/A		<b>Installation Instructions</b> <a href="#">FL20821_R3_II_Rapid Lok Fascia - Design Drawing.pdf</a> Verified By: Architectural Testing, Inc. (an Intertek company) - York, PA

[Back](#) [Next](#)

[Contact Us](#) :: [2601 Blair Stone Road, Tallahassee FL 32399](#) Phone: 850-487-1824

The State of Florida is an AA/EEO employer. [Copyright 2007-2013 State of Florida](#). :: [Privacy Statement](#) :: [Accessibility Statement](#) :: [Refund Statement](#)

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. \*Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click [here](#).

**Product Approval Accepts:**

